



Choker & Basket Sling

Type 1 Choker Sling

Web Width	Alloy Steel	Forgot Aluminum	Rated Capacities in Lbs.		
			Vertical	Choker	V. Basket
2"	CHS1-92	CHA1-92	3,100	2,480	6,200
	CHS2-92	N/A	6,200	4,960	12,400
	CHS3-92	N/A	8,300	6,600	16,600
	CHS4-92	N/A	12,400	9,920	24,800
3"	CHS1-93	CHA1-93	4,650	3,720	9,300
	CHS2-93	N/A	9,300	7,440	18,600
	CHS3-93	N/A	12,500	10,000	25,000
	CHS4-93	N/A	18,600	14,880	37,200
4"	CHS1-94	CHA1-94	6,200	4,960	12,400
	CHS2-94	N/A	11,000	8,800	22,000
	CHS3-94	N/A	16,000	12,800	32,000
	CHS4-94	N/A	22,000	17,600	44,000
6"	CHS1-96	CHA1-96	9,300	7,440	18,600
	CHS2-96	N/A	16,500	13,200	33,000
	CHS3-96	N/A	23,000	16,400	46,000
	CHS4-96	N/A	33,000	26,400	66,000
8"	CHS1-98	N/A	12,400	9,920	24,800
	CHS2-98	N/A	22,000	17,600	44,000
	CHS3-98	N/A	30,700	24,500	61,400
	CHS4-98	N/A	44,000	35,200	88,000
10"	CHS1-910	N/A	15,500	12,400	31,000
	CHS2-910	N/A	27,500	22,000	55,000
	CHS3-910	N/A	36,800	29,400	73,600
	CHS4-910	N/A	55,000	44,000	110,000
12"	CHS1-912	N/A	18,600	14,880	37,200
	CHS2-912	N/A	33,000	26,400	66,000
	CHS3-912	N/A	44,000	35,200	88,000
	CHS4-912	N/A	66,000	52,800	132,000



Metal hardware prolongs the life of slings prone to damage on the end of the sling.

Slings are available in nylon or polyester webbing.

Minimum 5:1 design factor.

Do not exceed rated capacities. The ratings must be reduced when lifting at angles of less than 90 degrees with the horizontal.



Choker & Basket Sling

Type 2 Basket Sling

Web Width	Alloy Steel	Forged Aluminum	Rated Capacities in Lbs.	
			Vertical	V. Basket
2"	BHS1-92	BHA1-92	3,100	6,200
	BHS2-92	N/A	6,200	12,400
	BHS3-92	N/A	8,300	16,600
	BHS4-92	N/A	12,400	24,800
3"	BHS1-93	BHA1-93	4,650	9,300
	BHS2-93	N/A	9,300	18,600
	BHS3-93	N/A	12,500	25,000
	BHS4-93	N/A	18,600	37,200
4"	BHS1-94	BHA1-94	6,200	12,400
	BHS2-94	N/A	11,000	22,000
	BHS3-94	N/A	16,000	32,000
	BHS4-94	N/A	22,000	44,000
6"	BHS1-96	BHA1-96	9,300	18,600
	BHS2-96	N/A	16,500	33,000
	BHS3-96	N/A	23,000	46,000
	BHS4-96	N/A	33,000	66,000
8"	BHS1-98	N/A	12,400	24,800
	BHS2-98	N/A	22,000	44,000
	BHS3-98	N/A	30,700	61,400
	BHS4-98	N/A	44,000	88,000
10"	BHS1-910	N/A	15,500	31,000
	BHS2-910	N/A	27,500	55,000
	BHS3-910	N/A	36,800	73,600
	BHS4-910	N/A	55,000	110,000
12"	BHS1-912	N/A	18,600	37,200
	BHS2-912	N/A	33,000	66,000
	BHS3-912	N/A	44,000	88,000
	BHS4-912	N/A	66,000	132,000



Fittings available in forged aluminum or alloy steel.

Slings are available in nylon or polyester webbing.

Minimum 5:1 design factor.

Do not exceed rated capacities.