



Heavy Duty Eye & Eye

Web Slings

Type 3 & 4 - EE

Web Width	No. Plys of Web	Part. No.	Rated Capacities in Lbs.			Eye Length
			Vertical	Choker	V. Basket	
1"	1	EE1-91	1,600	1,280	3,200	9"
	2	EE2-91	3,100	2,480	6,200	9"
	3	EE3-91	4,100	3,300	8,200	12"
	4	EE4-91	6,200	4,960	12,400	12"
2"	1	EE1-92	3,100	2,480	6,200	9"
	2	EE2-92	6,200	4,960	12,400	9"
	3	EE3-92	8,300	6,600	16,600	12"
	4	EE4-92	12,400	9,920	24,800	12"
3"	1	EE1-93	4,650	3,720	9,300	9"
	2	EE2-93	9,300	7,400	18,600	12"
	3	EE3-93	12,500	10,000	25,000	18"
	4	EE4-93	18,600	14,880	37,200	18"
4"	1	EE1-94	6,200	4,960	12,400	12"
	2	EE2-94	11,000	8,800	22,000	12"
	3	EE3-94	16,000	12,800	32,000	18"
	4	EE4-94	22,000	17,600	44,000	18"
6"	1	EE1-96	9,300	7,440	18,600	14"
	2	EE2-96	16,500	13,200	33,000	14"
	3	EE3-96	23,000	18,400	46,000	20"
	4	EE4-96	33,000	26,400	66,000	20"
8"	1	EE1-98	12,400	9,920	24,800	18"
	2	EE2-98	22,000	17,600	44,000	18"
	3	EE3-98	30,700	24,560	61,400	24"
	4	EE4-98	44,000	35,200	88,000	24"
10"	1	EE1-910	15,500	12,400	31,000	22"
	2	EE2-910	27,500	22,000	55,000	22"
	3	EE3-910	36,800	29,400	73,600	28"
	4	EE4-910	55,000	44,000	110,000	28"
12"	1	EE1-912	18,600	14,880	37,000	26"
	2	EE2-912	33,000	26,000	66,000	26"
	3	EE3-912	44,000	35,200	88,000	32"
	4	EE4-912	66,000	52,800	132,000	32"

Type 3 E&E web slings have a flat eye and are easier to remove from beneath a load.



Type 4 E&E web slings have twisted eyes that fit better in the bowl of a hook and work better in a choker hitch.



Type 3 & 4 web slings are tapered at 3" and wider unless otherwise specified.

Type 4 twisted eye slings are generally furnished unless otherwise specified.

Slings are available in nylon or polyester webbing.

Minimum 5:1 design factor.

Do not exceed rated capacities. The ratings must be reduced when lifting at angles of less than 90. Degrees with the horizontal.



Reversed Eye

Web Slings

Type 6 - RE

Web Width	Part. No.	Rated Capacities in Lbs.			Material Size	Eye Length
		Vertical	Choker	V. Basket		
2"	RE1-91	4,600	3,680	9,200	3"9800	9"
	RE2-91	7,700	6,160	15,400	3"9800	9"
	RE3-91	8,300	9,240	23,100	3"9800	9"
	RE4-91	11,500	9,280	23,200	3"9800	9"
3"	RE1-915	11,600	5,520	13,800	1.5"9800	12"
	RE2-915	6,900	9,120	23,200	1.5"9800	12"
	RE3-915	17,250	13,800	34,500	1.5"9800	12"
	RE4-915	17,400	13,920	34,800	1.5"9800	12"
4"	RE1-92	8,600	6,880	17,200	2"9800	18"
	RE2-92	14,500	11,600	29,000	2"9800	18"
	RE3-92	20,400	16,320	40,800	2"9800	18"
	RE4-92	23,000	18,400	46,000	2"9800	18"
6"	RE1-93	12,000	9,600	24,000	3"9800	14"
	RE2-93	17,400	13,920	34,800	3"9800	18"
	RE3-93	26,500	21,200	53,000	3"9800	20"
	RE4-93	34,000	27,200	68,000	3"9800	24"



Abrasion-resistant Cordura wear pads cover the eyes and side of the body, giving extra protection to prevent wear.

Slings are available in nylon or polyester webbing.

Minimum 5:1 design factor.

Do not exceed rated capacities. The ratings must be reduced when lifting at angles of less than 90 degrees with the horizontal.

Reversed eye slings are the most durable web slings available.

They provide superior performance in heavy-duty and abrasive applications.

They work well in all three hitch configurations.