



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

CABO POLIPROPILENO

3 STRAND, TWISTED, YELLOW



NOMINAL DIAMTER	NOMINAL CIRCUMFERENCE	FEET PER REEL	WORKING LOAD LIMIT	BREAKING STRENGTH IN POUNDS	NET WEIGHT PER 100' IN POUNDS	FEET PER POUND
1/4"	3/4"	600	113	1,130	1.20	83.3
1/4"	3/4"	1,200	113	1,130	1.20	83.3
5/16"	1"	600	171	1,710	1.80	55.6
5/16"	1"	1,200	171	1,710	1.80	55.6
3/8"	1-1/8"	600	244	2,440	2.80	35.7
3/8"	1-1/8"	1,200	244	2,440	2.80	35.7
7/16"	1-1/4"	600	352	3,160	3.80	26.3
1/2"	1-1/2"	600	420	3,780	4.70	21.3
1/2"	1-1/2"	1,200	420	3,780	4.70	21.3
9/16"	1-3/4"	600	575	4,600	6.10	16.4
5/8"	2"	600	700	5,600	7.50	13.3
5/8"	2"	1,200	700	5,600	7.50	13.3
3/4"	2-1/4"	600	1,090	7,650	10.7	9.4
3/4"	2-1/4"	1,200	1,090	7,650	10.7	9.4
7/8"	2-3/4"	600	1,490	10,400	15.0	6.7
1"	3"	600	1,800	12,600	18.0	5.6
1-1/8"	3-1/2"	600	2,360	16,500	23.8	4.2
1-1/4"	3-3/4"	600	2,700	18,900	27.0	3.7
1-1/2"	4-1/2"	600	3,820	26,800	38.4	2.6
1-3/4"	5-1/2"	300	5,550	38,800	59.0	1.7
2"	6"	600	6,700		69	1.45

Read important warnings and information preceding fittings section.