



**Cables Cadenas
y Bandas de México**
S.A. de C.V.



CABO MANILA

3- STRAND

Twisted, according to Federal Specification T-R-605b. Grade 1 Supplied in Coils.
Up to 3/4" x 600ft packed in cartons

Nominal Diameter	Nominal Circumference	Feet per coil	Working Load Limit in Pounds*	Breaking Strength in Pounds*	Net Weight per 100' in Pounds	Feet per Pound
1/4"	3/4"	1,250	54	540	2.0	50.0
1/4"	3/4"	2,500	54	540	2.0	50.0
5/16"	1"	1,200	90	900	2.9	34.5
3/8"	1 1/8"	600	122	1,220	4.1	24.4
3/8"	1 1/8"	1,200	122	1,220	4.1	24.4
7/16"	1 1/4"	600	176	1,580	5.25	19.1
1/2"	1 1/2"	600	264	2,380	7.5	13.3
1/2"	1 1/2"	1,200	264	2,380	7.5	13.3
5/8"	2"	600	496	3,960	13.3	7.5
5/8"	2"	1,200	496	3,960	13.3	7.5
3/4"	2 1/4"	600	695	4,860	16.7	6.0
3/4"	2 1/4"	1,200	695	4,860	16.7	6.0
13/16"	1 1/2"	600	835	5,850	19.5	5.13
7/8"	2 3/4"	600	995	6,950	22.4	4.46
1"	3"	600	1,160	8,100	27.0	3.70
1"	3"	1,200	1,160	8,100	27.0	3.70
1 1/8"	3 1/2"	600	1,540	10,800	36.0	2.78
1 1/8"	3 1/2"	300	1,540	10,800	36.0	2.78
1 1/8"	3 1/2"	350	1,540	10,800	36.0	2.78
1 1/4"	3 3/4"	600	1,740	12,200	41.6	2.40
1 1/4"	3 3/4"	300	1,740	12,200	41.6	2.40
1 1/4"	3 3/4"	350	1,740	12,200	41.6	2.40
1 1/2"	4 1/2"	600	2,380	16,700	60.0	1.67
2"	6"	600	4,000	28,000	108.0	.93

Breaking Strength listed for comparison only. Never exceed the Working Load Limit.



**Cables Cadenas
y Bandas de México**
S.A. de C.V.

CABO MANILA

4- STRAND

Twisted, according to Federal Specification T-R-605b.

Grade 1 Supplied in Coils.

Up to ¾" x 600ft packed in cartons

Nominal Diameter	Nominal Circumference	Feet per coil	Working Load Limit in Pounds*	Breaking Strength in Pounds*	Net Weight per 100' in Pounds	Feet per Pound
1"	3"	600	1,100	7,700	27.5	3.65
1 1/8"	3 1/2"	600	1,465	10,260	37.3	2.68
1 1/4"	3 3/4"	600	1,660	11,600	45.2	2.21



Breaking Strength listed for comparison only. Never exceed the Working Load Limit.